

Juniper Networks NetScreen-5XT



The Juniper Networks NetScreen-5XT is a feature rich enterprise-class network security solution with one Untrust 10/100 Ethernet port, four Trust 10/100 Ethernet ports, a console port and a modem port. Using the same firewall, VPN, and DoS mitigation technology as NetScreen's high-end central site products, the NetScreen-5XT is fully capable of securing a remote office, retail outlet, or a broadband telecommuter. The NetScreen-5XT supports dial-backup or dual Ethernet ports for redundant Internet connections when network uptime is business critical. The NetScreen-5XT has received Common Criteria and FIPS certifications.

Juniper Networks NetScreen-5XT

Maximum Performance and Capacity⁽¹⁾

Firewall performance	70 Mbps
3DES performance	20 Mbps
Deep Inspection performance	55 Mbps
Concurrent sessions	2,000
New sessions/second	2,000
Policies	100
Interfaces	5 10/100 Base-T

Mode of Operation

Layer 2 mode (transparent mode) ⁽²⁾	Yes
Layer 3 mode (route and/or NAT mode)	Yes
NAT (Network Address Translation)	Yes
PAT (Port Address Translation)	Yes
Home/work zones	Yes
Dual Untrust	Yes
Dial backup	Yes
Policy-based NAT	Yes
Virtual IP	1
Mapped IP	32
Users supported	10 or Unrestricted

Firewall

Number of network attacks detected	31
Network attack detection	Yes
DoS and DDoS protections	Yes
TCP reassembly for fragmented packet protection	Yes
Malformed packet protections	Yes
Deep Inspection firewall	Yes
Protocol anomaly	Yes
Stateful protocol signatures	Yes
DI Protocols supported	HTTP, FTP, SMTP, POP, IMAP, DNS, NetBIOS/SMB, MS-RPC, P2P, IM
Number of application attacks detected w/DI	over 600
Content Inspection	Yes
Embedded antivirus	No
Malicious Web filtering	up to 48 URLs
External Web filtering (Websense or SurfControl)	Yes
Integrated Web filtering	No

VPN

Concurrent VPN tunnels	up to 10
Tunnel interfaces	up to 10
DES (56-bit), 3DES (168-bit) and AES encryption	Yes
MD-5 and SHA-1 authentication	Yes
Manual Key, IKE, PKI (X.509)	Yes
Perfect forward secrecy (DH Groups)	1,2,5
Prevent replay attack	Yes
Remote access VPN	Yes
L2TP within IPSec	Yes
IPSec NAT traversal	Yes
Redundant VPN gateways	Yes
VPN tunnel monitor	Yes

Juniper Networks NetScreen-5XT

Firewall and VPN User Authentication

Built-in (internal) database - user limit	up to 100
3rd Party user authentication	RADIUS, RSA, SecurID, and LDAP
XAUTH VPN authentication	Yes
Web-based authentication	Yes

Logging/Monitoring

Syslog (multiple servers)	External, up to 4 servers
E-mail (2 addresses)	Yes
NetIQ WebTrends	External
SNMP (v1,v2)	Yes
Standard and custom MIB	Yes
Traceroute	Yes

Virtualization

Virtual Routers (VRs)	2, 3 with home/work
-----------------------	---------------------

Routing

OSPF/BGP dynamic routing	3 instances each
RIPv1/v2 dynamic routing	3 instances
Static routes	1,024
Source-based routing	Yes
Equal cost multi-path routing	Yes

High Availability (HA)

Dial backup	Yes
Dual Untrust	Yes

VoIP

H.323 ALG	Yes
SIP ALG	Yes
NAT for H.323/SIP	Yes

IP Address Assignment

Static	Yes
DHCP, PPPoE client	Yes
Internal DHCP server	Yes
DHCP relay	Yes

PKI Support

PKI certificate requests (PKCS 7 and PKCS 10)	Yes
Automated certificate enrollment (SCEP)	Yes
Online Certificate Status Protocol (OCSP)	Yes
Self Signed Certificates	Yes
Certificate Authorities Supported	
Verisign	Yes
Entrust	Yes
Microsoft	Yes
RSA Keon	Yes
iPlanet (Netscape)	Yes
Baltimore	Yes
DOD PKI	Yes

**Juniper Networks
NetScreen-5XT**

System Management

WebUI (HTTP and HTTPS)	Yes
Command Line Interface (console)	Yes
Command Line Interface (telnet)	Yes
Command Line Interface (SSH)	Yes, v1.5 and v2.0 compatible
NetScreen-Security Manager	Yes
All management via VPN tunnel on any interface	Yes
Rapid deployment	Yes

Administration

Local administrators database	20
External administrator database	RADIUS/LDAP/SecurID
Restricted administrative networks	6
Root Admin, Admin, and Read Only user levels	Yes
Software upgrades	TFTP/WebUI/SCP/NSM
Configuration Roll-back	Yes

Traffic Management

Guaranteed bandwidth	Yes
Maximum bandwidth	Yes
Priority-bandwidth utilization	Yes
DiffServ stamp	Yes

Dimensions and Power

Dimensions (H/W/L)	1.25/8.125/5 inches
Weight	1.5 lbs.
Rack mountable	Yes, with separate kit
Power Supply (AC)	12 VDC, 12 W
90 to 264 VAC to power supply with regional linear supply	12VDC, 12 W
Power Supply (DC)	No

License Options: The NetScreen-5XT is available in two models to support different numbers of users.

10 User Product License: The 10 user product license (NetScreen-5XT 10-User) supports 10 users.

Unrestricted Product License: The unrestricted product license (NetScreen-5XT Elite) support an unlimited number of users.

Certifications

- Safety Certifications
 - UL, CUL, CSA, CB
- EMC Certifications
 - FCC class B, BSMI Class B, CE class B, C-Tick, VCCI class B

Environment

- Operational temperature: 23° to 122° F, -5° to 50° C
- Non-operational temperature: -4° to 158° F, -20° to 70° C
- Humidity: 10 to 90 % non-condensing

MTBF (Belcore model)

NetScreen-5XT: 8.5 years

Security

- Common Criteria: EAL4
- FIPS 140-2: Level 2
- ICSA Firewall and VPN

Ordering Information

Product		Part Number
Juniper Networks NetScreen-5XT 10 User		
NetScreen-5XT	US power cord	NS-5XT-001
NetScreen-5XT	UK power cord	NS-5XT-003
NetScreen-5XT	European power cord	NS-5XT-005
NetScreen-5XT	Japanese power cord	NS-5XT-007
Upgrade from NetScreen-5XT 10-user to NetScreen-5XT Elite		NS-5XT-ELU
Juniper Networks NetScreen-5XT Elite (unrestricted users)		
NetScreen-5XT Elite	US power cord	NS-5XT-101
NetScreen-5XT Elite	UK power cord	NS-5XT-103
NetScreen-5XT Elite	European power cord	NS-5XT-105
NetScreen-5XT Elite	Japanese power cord	NS-5XT-107
Rack mount kit for 2 NetScreen-5XTs		NS-5XT-RMK

(1) Performance and capacity provided are the measured maximums under ideal testing conditions. May vary by deployment and features enabled.
 (2) The following features are not supported in Layer 2 (transparent mode): NAT, PAT, policy based NAT, virtual IP, mapped IP, OSPF, BGP, RIPv2, and IP address assignment. Transparent mode only works in trust/untrust mode.



CORPORATE HEADQUARTERS AND SALES HEADQUARTERS FOR NORTH AND SOUTH AMERICA
 Juniper Networks, Inc.
 1194 North Mathilda Avenue
 Sunnyvale, CA 94089 USA
 Phone: 888-JUNIPER (888-586-4737)
 or 408-745-2000
 Fax: 408-745-2100
www.juniper.net

EAST COAST OFFICE
 Juniper Networks, Inc.
 10 Technology Park Drive
 Westford, MA 01886-3146 USA
 Phone: 978-589-5800
 Fax: 978-589-0800

ASIA PACIFIC REGIONAL SALES HEADQUARTERS
 Juniper Networks (Hong Kong) Ltd.
 Suite 2507-11, Asia Pacific Finance Tower
 Citibank Plaza, 3 Garden Road
 Central, Hong Kong
 Phone: 852-2332-3636
 Fax: 852-2574-7803

EUROPE, MIDDLE EAST, AFRICA REGIONAL SALES HEADQUARTERS
 Juniper Networks (UK) Limited
 Juniper House
 Guildford Road
 Leatherhead
 Surrey, KT22 9JH, U. K.
 Phone: 44(0)1372-385500
 Fax: 44(0)1372-385501

Copyright 2004, Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, NetScreen, NetScreen Technologies, the NetScreen logo, NetScreen Global Pro, ScreenOS, and GigaScreen are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The following are trademarks of Juniper Networks, Inc.: ERX, ESP, E-series, Instant Virtual Extranet, Internet Processor, J2300, J4300, J6300, JProtect, J-series, J-Web, JUNOS, JUNOScope, JUNOScript, JUNOSE, MS, M7i, M10, M10i, M20, M40, M40e, M160, M320, M-series, MMD, NetScreen-5GT, NetScreen-5XP, NetScreen-5XT, NetScreen-25, NetScreen-50, NetScreen-204, NetScreen-208, NetScreen-500, NetScreen-5200, NetScreen-5400, NetScreen-IDP 10, NetScreen-IDP 100, NetScreen-IDP 500, NetScreen-Remote Security Client, NetScreen-Remote VPN Client, NetScreen-SA 1000 Series, NetScreen-SA 3000 Series, NetScreen-SA 5000 Series, NetScreen-SA Central Manager, NetScreen Secure Access, NetScreen-SM 3000, NetScreen-Security Manager, NMO-RX, SDX, Stateful Signature, T320, T640, and T-series. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners. All specifications are subject to change without notice. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.